

S8R

Inspire Series

The new Inspire Series with Rain Shower.

Relaxation at its best.



**Energy Saving
Inverter DC Pump***



**Splash Proof
Casing**



**Easy Clean
Durable Nozzles**



**Thermal Safety
Cut-Off**



**Double Relay
ELCB**



**Quiet
Operation***



**ELCB Test
Button**



**Flow Rate :
Up to 400%***



**Easy To
Install**



MADE IN MALAYSIA



Suruhanjaya Tenaga



Sirim Malaysia
Certified to :
MSIEC60335-1:1995+
MS1597 : Part 2-35: 2003

* For S8R ESP only

Instant water heater features and technical specifications

| Innovative Features | | S8R <i>ESP</i> | S8R <i>EP</i> | S8R <i>E</i> |
|-------------------------------------|------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Double relay ELCB | | ● | ● | ● |
| Silent booster pump | | ● | – | – |
| AC booster pump | | – | ● | – |
| Standard Features | | | | |
| Auto flow sensor switch | | ● | ● | ● |
| Safety anti-scalding device | | ● | ● | ● |
| Stop valve | | ● | ● | ● |
| Rain shower | | ● | ● | ● |
| 5-way massage spray hand shower | | ● | ● | ● |
| Stepless electronic power control | | ● | ● | ● |
| Sleek and slim design | | ● | ● | ● |
| Leak proof heater tank | | ● | ● | ● |
| Splash proof casing IP25 | | ● | ● | ● |
| Built-in ELCB with surge protector | | ● | ● | ● |
| 5 years warranty (Inverter DC pump) | | ● | – | – |
| 400% stronger water flow rate | | ● | – | – |
| 60% power saving on pump | | ● | – | – |
| Specifications | | | | |
| Power rating (kW) | | 4.3 | 3.8 | 3.7 |
| Voltage (V) | | 240 | 240 | 240 |
| Frequency (Hz) | | 50 | 50 | 50 |
| Minimum water pressure | (kgf/cm ²) | 0.14 | 0.14 | 0.14 |
| | (psi) | 2 | 2 | 2 |
| Maximum water pressure | (kgf/cm ²) | 3.87 | 3.87 | 3.87 |
| | (psi) | 55 | 55 | 55 |
| Water connection | (mm) | 15 | 15 | 15 |
| | (inches) | 1/2 BSP | 1/2 BSP | 1/2 BSP |
| Water temperature control | | Variable stepless electronic control | Variable stepless electronic control | Variable stepless electronic control |
| Pump rating (W) | | 48 (24V d.c.) | 120 | – |
| Product Dimensions | | | | |
| Depth (mm) | | 95 | 95 | 95 |
| Width (mm) | | 235 | 235 | 235 |
| Height (mm) | | 375 | 375 | 375 |
| Weight (kg) | | 3.2 | 3.8 | 2.8 |



Gloss White



Platinum Grey



Matt Black

“●” featured

“–” not featured

Distributed by:

BEEBEST MARKETING SDN. BHD. (649240-W)

No. 1, Jalan Astaka U8/83, Bukit Jelutong,
40150 Shah Alam, Selangor.

Tel : **03-7846 3133 (Hunting Line)**

03-7847 6133

03-7846 6133

Fax : 03-7845 9133

Email : enquiry@beebest.com.my

www.beebest.com.my

Manufactured by:

BEEBULL ENGINEERING SDN. BHD. (317477-U)

Tel : 03-7845 8188

Fax : 03-7845 2188

Email : enquiry@beebull.com

www.beebull.com

SINCE
1993