



Features



Today's Lifestyle Shower 

Quiet Operation ¹



Splash Proof Casing 

Double Relay ELCB



Energy Saving Inverter DC Pump 


Available in Delightful Colour Choices



Easy Clean Durable Nozzles 

ELCB Test/Reset & Pump Buttons



Easy to Operate 

Flow Rate : Up to 400%²



Thermal Safety Cut-Off 

Easy to Install

¹For iSENSE ESP only

²For iSENSE EP and ESP only

Specifications

Innovative Features	iSENSE RS	ESP	iSENSE RS
<ul style="list-style-type: none"> ▪ Double relay self test ELCB _ Quiet DC booster pump AC booster pump - 			
Standard Features			
<ul style="list-style-type: none"> ▪ Auto flow sensor switch ▪ Safety anti-scalding device ▪ Stop valve ▪ Rain shower ▪ 3-way massage spray hand shower ▪ Electronic touch power selection ▪ Sleek and slim design ▪ Leak proof heater tank ▪ Splash proof casing IP25 ▪ Built-in ELCB with surge protector _ 5 years warranty (Inverter DC pump) _ Up to 400% stronger water flow rate _ 60% power saving pump 			
Specifications			
Power rating (kW)	3.7	3.7	
Voltage (V)	240	240	
Frequency (Hz)	50	50	
Minimum water pressure (kgf/cm ²)		0.14	0.14

(psi)	2	2	
Maximum water pressure(kgf/cm ²)		3.87	3.87
(psi)	55	55	
Water connection	(mm)	15	15
(inches)	1/2 BSP	1/2 BSP	
Water temperature control	Electronic touch panel selection touch panel selection		
Pump rating	48 (24V d.c.)	-	
Product Dimensions			
Depth (mm)	100	100	
Width (mm)	240	240	
Height	390	390	
Weight (kg)	4.6	4.2	

