



Features



Energy Saving Inverter DC Pump*

Quiet Operation*



Splash Proof Casing



ELCB Test Button



Easy Clean Durable Nozzles

Flow Rate : Up to 400%*



Thermal Safety Cut-Off



Easy to Install



Double Relay ELCB

* For Angel ESP only

Specifications

| Innovative Features | Angel | ESP | Angel |
|---|----------|---------|-------|
| <ul style="list-style-type: none"> ▪ Double relay ELCB ▪ Quiet DC booster pump ▪ AC booster pump | | | |
| Standard Features | | | |
| <ul style="list-style-type: none"> ▪ Auto flow sensor switch ▪ Thermal safety cut-off ▪ 3 in 1 stop valve ▪ 3-way massage spray hand shower ▪ Stepless electronic power control ▪ Sleek and slim design ▪ Leak proof heater tank ▪ Splash proof casing IP25 ▪ Up to 400% stronger water flow rate ▪ 60% power saving pump | | | |
| Specifications | | | |
| Power rating (kW) | 4.3 | 3.7 | |
| Voltage (V) | 240 | 240 | |
| Frequency (Hz) | 50 | 50 | |
| Minimum water pressure (kgf/cm ²) | | 0.14 | 0.14 |
| (psi) | 2 | 2 | |
| Maximum water pressure(kgf/cm ²) | | 3.87 | 3.87 |
| (psi) | 55 | 55 | |
| Water connection | (mm) | 15 | 15 |
| (inches) | 1/2 BSP | 1/2 BSP | |
| Water temperature control | Variable | | |
| stepless electronic control | | | |
| stepless electronic control | | | |

control

Pump rating 48W (24V d.c.) -

Product Dimensions

| | | |
|-------------|-----|-----|
| Depth (mm) | 90 | 90 |
| Width (mm) | 230 | 230 |
| Height | 370 | 370 |
| Weight (kg) | 3.3 | 3 |

