



## Features



Energy Saving Inverter DC Pump\*

Quiet Operation\*



Splash Proof Casing 

ELCB Test Button



Easy Clean Durable Nozzles 

Flow Rate : Up to 400%\*



Thermal Safety Cut-Off 

Easy to Install



Double Relay ELCB

\* For Angel ESP only

## Specifications

<b>Innovative Features</b>	<b>Angel</b>	<b>ESP</b>
Double relay ELCB <input checked="" type="checkbox"/>		
Quiet DC booster pump <input checked="" type="checkbox"/>		
AC booster pump -		
<b>Standard Features</b>		
Auto flow sensor switch <input checked="" type="checkbox"/>		
Thermal safety cut-off <input checked="" type="checkbox"/>		
3 in 1 stop valve <input checked="" type="checkbox"/>		
3-way massage spray hand shower <input checked="" type="checkbox"/>		
Stepless electronic power control <input checked="" type="checkbox"/>		
Sleek and slim design <input checked="" type="checkbox"/>		
Leak proof heater tank <input checked="" type="checkbox"/>		
Splash proof casing IP25 <input checked="" type="checkbox"/>		
Up to 400% stronger water flow rate <input checked="" type="checkbox"/>		
60% power saving pump <input checked="" type="checkbox"/>		
<b>Specifications</b>		
Power rating (kW)	4.3	
Voltage (V)	240	
Frequency (Hz)	50	
Minimum water pressure (kgf/cm <sup>2</sup> )		0.14
(psi)	2	
Maximum water pressure(kgf/cm <sup>2</sup> )		3.87
(psi)	55	
Water connection (mm)		15
(inches)	1/2 BSP	
Water temperature control	Variable	
stepless		
electronic		
control		
Pump rating	48W (24V d.c.)	
<b>Product Dimensions</b>		
Depth (mm)	90	
Width (mm)	230	
Height	370	
Weight (kg)	3.3	

## Downloads

### Downloads

{phocadownload view=file|id=6|target=s}

